



Especificaciones	GT-22	GT-25	GT-30	GT-40
Dimensiones de mesa de trabajo	7.8" x 17.7" (200 x 450 mm)	10" x 20" (254 x 508 mm)	12" x 25" (305 x 635 mm)	16" x 32" (406 x 813 mm)
Máxima capacidad de carga	280 lbs (128 kg)	400 lbs (180 kg)	600 lbs (270 kg)	1100 lbs (500 kg)
Recorrido longitudinal	19.6" (500 mm)	22" (560 mm)	30" (765 mm)	32.6" (830 mm)
Recorrido transversal	9.44" (240 mm)	10.82" (275 mm)	13.3" (340 mm)	16.5" (420 mm)
Distancia máxima del centro de husillo a mesa	N/A	17.7" (450 mm)	22.8" (580 mm)	22.8" (580 mm)
Avance automático transversal	N/A	0.004 - 0.315" (0.1 - 8 mm)	0.004 - 0.315" (0.1 - 8 mm)	0.004 - 0.315" (0.1 - 8 mm)
Velocidad de oscilación eje X	N/A	200 - 980 IPM (5 - 25 m/min)	200 - 980 IPM (5 - 25 m/min)	200 - 980 IPM (5 - 25 m/min)
Motor de husillo	2 hp	3 hp	5 hp	5 hp
Velocidad de husillo	2850 rpm	2850 rpm	1440 rpm	1440 rpm
Rueda de rectificado (ODxTxID)	7.87" x 0.5" x 1.25" (200 x 13 x 31.75 mm)	7.87 x 0.78 x 1.25" (200 x 20 x 31.75 mm)	13.8 x 1.5 x 5" (350 x 40 x 127 mm)	13.8 x 1.5 x 5" (350 x 40 x 127 mm)
Bomba de soluble	1/8 hp	1/8 hp	1/4 hp	1/4 hp
Peso de la máquina	1985 lbs (100 kg)	400 lbs (1900 kg)	5900 lbs (3000 kg)	7900 lbs (3650 kg)

Accesorios	GT-22	GT-25	GT-30	GT-40
Visualizador y escalas digitales en dos ejes	✓	✓	✓	✓
Chuck electromagnético	✓	✓	✓	✓
Sistema de soluble	✓	✓	✓	✓
Lámpara LED	✓	✓	✓	✓
Bases niveladoras	✓	✓	✓	✓
Caja de herramientas	✓	✓	✓	✓